

Bip - Bug #212

When global option log is disabled, query are not backlogged

2011-04-07 02:55 - Pierre-Louis Bonicoli

Status:	Resolved	Start date:	2011-04-07
Priority:	Normal	Due date:	
Assignee:	Pierre-Louis Bonicoli	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:	0.8.8	Branch:	
Patch Available:	No	Security:	No
Found in Versions:	<= 0.8.7	Help Needed:	
Confirmed:	Yes		

Description

How to reproduce

1. set 'log' option to 'false' in bip.conf
2. (re)start bip, don't connect any client to bip
3. send a message with another user in a channel where bip is here
4. send a private message to bip user with another user
5. connect a client to bip
6. message in channel is backlogged
7. private message is not backlogged only "End of backlog" is displayed

History

#1 - 2011-04-07 03:15 - Pierre-Louis Bonicoli

- *pilou_bip*: nickname of bip user
- *Pilou*: other user

1. with *log = true*;
07-04-2011 02:44:05 [freenode] backlogging: pilou_bip
in function *real_write_all* this line is sent by bip daemon to client: [:Piloulbip@b.i.p PRIVMSG pilou_bip :02:44:01> test message](#)
2. with *log = false*;
07-04-2011 02:44:05 [freenode] backlogging: pilou_bip
in function *real_write_all* this line is sent by bip daemon to client: [:Piloulbip@b.i.p PRIVMSG Pilou :02:50:35> test message](#)

When log is disabled, private backlogged messages are malformed.

#2 - 2011-04-12 01:21 - Pierre-Louis Bonicoli

- Status changed from New to Resolved
- % Done changed from 0 to 100
- Found in Versions set to <= 0.8.7

Fixed by [f19e1f6209387e221a7f2535937f76dfc4938e60](#)