

## Bip - Bug #313

### Bip fails to build without ssl

2013-11-04 08:48 - Pierre-Louis Bonicoli

<b>Status:</b>	Resolved	<b>Start date:</b>	2013-11-04
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Pierre-Louis Bonicoli	<b>% Done:</b>	100%
<b>Category:</b>		<b>Estimated time:</b>	0:00 hour
<b>Target version:</b>	0.9.0	<b>Branch:</b>	
<b>Patch Available:</b>	Yes	<b>Security:</b>	No
<b>Found in Versions:</b>		<b>Help Needed:</b>	No
<b>Confirmed:</b>	Yes		

**Description**

Reported by Whoopie.

Bip fails to build without ssl.

How to reproduce:

```
autoreconf -i -Wall
./configure --enable-maintainer-mode --without-openssl
make
```

Error is:

```
depbased=`echo src/bip.o | sed 's|[^/]*$|.deps/&|;s|\..o$||'`;
gcc -DHAVE_CONFIG_H -I. -I./src -Wall -Wextra -Werror -g -O2 -fPIE -MT src/bip.o -MD -MP -M
F $depbased.Tpo -c -o src/bip.o src/bip.c &&\
mv -f $depbased.Tpo $depbased.Po
src/bip.c: In function 'adm_bip':
src/bip.c:2259:3: error: implicit declaration of function 'adm_trust' [-Werror=implicit-function-d
eclaration]
    return adm_trust(ic, line);
           ^
cc1: all warnings being treated as errors
make[1]: *** [src/bip.o] Error 1
make[1]: Leaving directory `/tmp/bip2'
make: *** [all] Error 2
```

Whoopie suggested this patch:  
[http://freetz.org/browser/trunk/make/bip/patches/111-no\\_ssl.patch](http://freetz.org/browser/trunk/make/bip/patches/111-no_ssl.patch)

#### Associated revisions

Revision 8d3539a7 - 2013-11-04 08:49 - Pierre-Louis Bonicoli

Fix --without-openssl build

Reported & fixed by Whoopie, thanks to him !  
Closes #313

#### History

**#1 - 2013-11-04 08:54 - Pierre-Louis Bonicoli**

- *Status changed from New to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset [8d3539a7d0eed8f9074eb5ec42c9f9d39d6b4af4](#).